

MATERIAL SAFETY DATA SHEET

MSDS Name: RAMSET SOUND CONTROL SEALANT

MSDS Number: SC200

MSDS Last Updated: 12/15/2006

Page 1/4

1. PRODUCT AND COMPANY INFORMATION

Product Name: RAMSET SOUND CONTROL SEALANT
CAS Number: MIXTURE
Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPI: B

Company Identification: ITW RAMSET
700 HIGH GROVE BLVD.
GLENDALE HEIGHTS, IL 60139

Telephone/Fax: (800) 899-7890 / (630) 350-1858
Chemtrec (24 Hour): (800) 424-9300

Trade Name: SOUND CONTROL SEALANT
DOT Hazard Class
UN Number: NON REG

2. HAZARDOUS INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
SILICA, QUARTZ	14808-60-7	<0.5	Y

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death.

Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans.

3. PHYSICAL DATA

Appearance/Color: WHITE
Boiling Range: 212°F
Evaporation Rate: SLOWER THAN N-BUTYL ACETATE
% Volatile Weight: 35.2%
% Volatile Volume: NOT AVAILABLE
Specific Gravity: 1.38
Weight/Volume Measure: 11.79
EPA Method 24 VOC: 175.8 g/L

Photo Chem Reactive Only VOC:107.1

MATERIAL SAFETY DATA SHEET

MSDS Name: RAMSET SOUND CONTROL SEALANT

MSDS Number: SC200

MSDS Last Updated: 12/15/2006

Page 2/4

4. FIRE AND EXPLOSION HAZARD DANGER

Flammability Class: IIIB
Flash Range: NOT APPLICABLE
Explosive Range: NOT APPLICABLE

EXTINGUISHING MEDIA:

Water spray, carbon dioxide, dry chemical or foam.

SPECIAL FIREFIGHTING PROCEDURES:

After water evaporates, remaining material will burn. Breathing apparatus when fighting fires in enclosed areas.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Decomposition products may cause a health hazard.

5. HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL:

See Section 8

EFFECTS OF OVEREXPOSURE:

INHALATION: Materials are low in volatility and therefore not likely to pose a problem.

EYES: May cause Minor irritation.

SKIN: Not likely to be absorbed in toxic amounts. Avoid skin contact as much as possible; upon repeated contact, slight skin irritation may occur.

INGESTION: None reported, not a likely route of entry.

FIRST AID:

INHALATION: Get fresh air.

EYES: flush with water for at least 15 minutes.

SKIN: Wash with mild soap and water; apply a mild cream.

INGESTION: Small amounts are not expected to produce adverse health effects. Larger amounts should be recovered by aspiration. Call a physician.

6. REACTIVITY DATA

Stability: THIS PRODUCT IS STABLE

Hazardous Polymerization: HAZARDOUS POLYMERIZATION WILL NOT OCCUR

INCOMPATIBILITY:

Strong acids or alkaline materials.

CONDITIONS TO AVOID:

None known

HAZARDOUS DECOMPOSITION PRODUCTS:

Fumes, smoke, carbon monoxide, carbon dioxide in the case of incomplete combustion.

MATERIAL SAFETY DATA SHEET

MSDS Name: RAMSET SOUND CONTROL SEALANT

MSDS Number: SC200

MSDS Last Updated: 12/15/2006

Page 3/4

7. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Confine to small area. Use absorbent to clean up. Place in container for disposal.

WASTE DISPOSAL METHOD:

Dispose in accordance with federal, state and local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

SILICA, QUARTZ	0.10 mg/M3	N/est	N/est	N/est	N/est
----------------	------------	-------	-------	-------	-------

RESPIRATORY PROTECTION:

None required for normal use.

VENTILATION:

Natural ventilation should be adequate under normal conditions.

PROTECTIVE GLOVES:

Impervious gloves, if needed, to avoid repeated or prolonged skin contact.

EYE PROTECTION:

Safety glasses. Face shield as necessary if spraying.

OTHER PROTECTIVE EQUIPMENT:

Not likely to be needed.

9. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not store above 125°F or below freezing or damage may occur to product.

OTHER PRECAUTIONS:

For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe fumes. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Close all containers when not in use. Empty containers must not be washed and re-used for any purpose. Contact lens wearers take appropriate precautions. Wash hands thoroughly after handling.

For spray applications, use only with approved spray equipment.

For flammable products, vapors may cause flash fire or ignite explosively. To prevent buildup of vapors, use adequate ventilations (e.g. open all window and doors to achieve cross-ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container.

MATERIAL SAFETY DATA SHEET

MSDS Name: RAMSET SOUND CONTROL SEALANT

MSDS Number: SC200

MSDS Last Updated: 12/15/2006

Page 4/4

10. ADDITIONAL REGULATORY INFORMATION

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number	Percent
SILICA, QUARTZ	14808-60-7	<0.5

11. DISCLAIMER

***** NOTICE *****

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW RAMSET. The data on this sheet relates only to the specific material designated herein. ITW RAMSET assumes no legal responsibility for use or reliance upon these data.